



PRODUCT SPECIFICATIONS

43" 7000XE Series



43" Panel Specifications

Size 1092 mm

Panel Aspect Ratio 16:9

Display Area

941.184 mm x 529.416 mm

Resolution 3840(H) x 2160(V) **Pixel Pitch** 0.2451 mm x 0.2451 mm

Back Light Unit ELED 8 ms **Display**

Response Time (bit) **Brightness** 450

Refreshing Frequency 60Hz

Contrast Ratio 1200:1 **Viewing**

Angle 178°

Life Time > 50,000 Hours

7000XE SERIES INTERACTIVE PANELS

The all-new 7000XE Series with PCAP technology for superior multi-touch control.



4K VIEWING EXPERIENCE



RICH AUDIO EXPERIENCE



INTUITIVE TOUCH EXPERIENCE



COLLABORATION SOFTWARE WITHOUT SUBSCRIPTION



INTEGRATED DEVICE CASTING



PANEL MANAGEMENT WITH VIDEO BROADCAST



INTEGRATED MESSAGING AND ALERT NOTIFICATIONS

PANEL AUDIO

Sound Channel	2:1
Output Power	2 x 10W+15W

PANEL CONNECTIONS

HDMI Output*	1
USB 2.0 (shared across all inputs)	3
USB 3.0*(shared across all inputs)	3
USB-C port (45W PD)	1
Touch Input	2
HDMI Input	4
VGA Input	1
Audio Input	1
RS232 Port	1
Audio Output	1
RJ45 Port with LAN Pass Through to PC	1
SPDIF	1

PANEL INTERACTIVITY

Sensing Type	Capacitive recognition
Compatibility	Windows10/Windows8/Windows7/ WindowsXP/Linux/MacOSX/Android/ Chrome
Touch Point	10 points writing 20 points touch
Minimum Object Size	6 mm
Touch Tool	Finger, Capacitive stylus
Response Time	8 ms
Accuracy	±1 mm 90% area
Palm Rejection	Support
Pressure Sensitivity	Support
Simultaneous Writing	Double writing and double pens
Glass Type	Toughened glass with Level 7 of Mohs standard
Interpolation Resolution	32768(W) x 32768(D)

PANEL OPERATING SYSTEM

System Version	Android 8.0
CPU	A73x2 + A53x2
GPU	Mali G51x4
RAM	4GB
ROM	32GB

PANEL AMBIENT

Operation Temperature	0°C – 40°C
Operation Humidity	10% – 90%
Storage Temperature	-20°C – 60°C
Storage Humidity	10% – 90%
Altitude	Below 5000 m

POWER

Power Requirements	100-240V ~ 50/60Hz 3.0A
Standby Power	≤0.5W
Overall Power (nominal power)	300W

PHYSICAL SPECIFICATION

Key Location & Number	Right side physical key
Dimension L*H*D*	1003 mm x 599 mm x 72 mm
Dimension (package) L*W*H	1119 mm x 187 mm x 1717 mm
Net Weight	28.25 kg
Gross Weight	30.95 kg
Machine + Wall Mount Thickness	102 mm WIB9060G
Wall-hanging Screw Spec	M8 x 25 mm
VESA	400 x 300 mm

ACCESSORIES

American standard power cord, USB touch cable (Type A-B), HDMI cable, remote control, writing pens (2), AAA batteries (2), Quick Start Guide

PC MODULE (OPTIONAL)

Type	Detachable PC module
Model	CTI-PCMOD-PC55-ST CTI-PCMOD-PC67-VP
CPU	Intel® Core™ i5 8400 CPU Intel® Core™ i7 8700 CPU
RAM	DDR4 8GB DDR4 16GB
SSD	256GB 512GB
Graphics	Integrated Intel® HD UHD Graphics 630
Chipset	Intel® H310 Intel® Q470
Sound Card	Integrated High Definition Audio Stereo
Networking	10/100/1000MB
WiFi Version	802.11ac 802.11ax
WiFi Frequency	2.4GHz/5GHz
WiFi Working Distance	0 ~ 45 m 0 ~ 90 m
Bluetooth Version	Bluetooth 2.1; 3.0; 4.0; 5.0
Bluetooth Working Frequency	2.4GHz
Bluetooth Working Distance	0 ~ 10 m
Operating System	Not included
Earphone Output	1
USB 2.0 3.0	6
Microphone Input	1
LAN(RJ45)	1
Display Port Output	1
VGA Output	
HDMI Output	1

PANEL WARRANTY OPTIONS

Standard	1 year
Registered	3 years
Optional	5 years





PRODUCT SPECIFICATIONS

Mini Convertible Stand

Features:

Fully adjustable height & angle allows for lower height settings

Electric powered stand makes adjustments simple

Quiet electrical motor

C-shaped base provides greater accessibility for all users

Intelligent, anti-collision design

3-year warranty on all components

ADA compliant



Part No:	Shipping size	Shipping weight
CTI-STAND-MINC	30.8" x 23.7" x 21.6" (786 x 602 x 548 mm)	88.2 lbs (40 kg)

